



ROWE SCIENTIFIC
PTY LTD www.rowe.com.au


For accuracy and professionalism

*Providing laboratory supplies
to the scientific community
across Australia since 1987.*

*We are proudly a 100%
Australian owned company.*






air release properties of petroleum oils



automated air release value analyzer

- Conforms to ASTM D3427, IP 313 and related specifications
- Integrated Touch Screen Control Panel
- Automatic lift system that moves test vessel from air source to balance sinker
- Automatic calculation of final sample density for determination of air release value
- Integrated Circulation bath with Water Level Indicator
- Integrated Balance
- Secure Clamp Mechanism of the Air Tube
- Automatic Jacketed Test Vessel Draining
- Safety Shield
- LIMS Compatibility

The Koehler Air Release Value Apparatus consists of a test vessel and air flow control equipment for delivering heated air at the specified flow rate to a lubricating oil sample maintained at constant temperature. Integrated Touch Screen Control panel guides user from start to finish of test operation and provides density calculation and timing operation for measuring the air release value of the test sample. Drying oven available as additional accessory for warming test oil at temperatures of up to 100°C; Integrated circulating bath and balance, and air bath for sinker; compressed air heater, overtemperature and overpressure protection circuitry. Automatically measures the time for air release.



test method

The ability of a turbine, hydraulic, or lubricating oil to separate entrained air is a key performance characteristic in applications where agitation causes a dispersion of air bubbles in the oil. To determine air release properties, the sample is heated to a specified test temperature and blown with compressed air. After the air flow is stopped, the time required for the air entrained in the oil to reduce in volume to 0.2% is the air bubble separation time.

dimensions W x D x H, in. (cm)
24x23x34 (60.96x58.42x86.36)

Net Weight: 115 lb (53 kg)

specifications

Conforms to the Specifications of:
ASTM D3427; IP 313; ISO 9120; DIN 51381; NF E 48-614;
NF T 60-149; BS 2000 Part 313

Temperature Range: Ambient to 75 °C (167 °F)
Sample Temperature Stability: ± 0.1 C
Air Temperature Stability: ± 0.2 C
Density: ± 0.001 g/ml

Electrical Requirements:
115V, 60Hz, Single Phase
230V, 50/60Hz, Single Phase

Included Accessories
Sinkers, 5mL and 10 mL
Integrated Balance
Integrated Circulator
Tubing and Fittings
Platinum Wire
Jacketed Test Vessel



South Australia & NT
Ph: (08) 8186 0523
rowesa@rowe.com.au

Queensland
Ph: (07) 3376 9411
roweqld@rowe.com.au

Victoria & Tasmania
Ph: (03) 9701 7077
rowevic@rowe.com.au

New South Wales
Ph: (02) 9603 1205
rowensw@rowe.com.au

Western Australia
Ph: (08) 9302 1911
rowewa@rowe.com.au