Multielement Standards in tartaric/ HCI/ NaCI ROWE SCIENTIFIC

Chemwatch Hazard Alert Code: 2

Issue Date: **20/12/2023** Print Date: **20/12/2023** L.GHS.AUS.EN.E

Chemwatch: **5647-26**Version No: **4.1**Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

| Product Identifier | |
|-------------------------------|--|
| Product name | Multielement Standards in tartaric/ HCl/ NaCl |
| Chemical Name | Not Applicable |
| Synonyms | CB3726; CB3756; CI1557: CI1558; CI1559; CI1560; CI1561; CI1562; CI1563; CI1567; CL2081; CL2082; CL2083; CL2084; CL2087; CM3865; CM3866; CM3867; CM3869; CM3870; CM3871; CM3875; CM3876; CM3877; CM3878; CM3879; CM3880; CM3881; CM3882; CM3883; CM3885; CR0822; CR0823; CR0824; CS7086; CS7087; CS7089; CS7090 |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Laboratory chemical |
|--------------------------|---|
| | Use according to manufacturer's directions. |

Details of the manufacturer or supplier of the safety data sheet

| | · |
|-------------------------|--|
| Registered company name | ROWE SCIENTIFIC |
| Address | 11 Challenge Boulevard Wangara WA 6065 Australia |
| Telephone | +61 8 9302 1911 |
| Fax | +61 8 9302 1905 |
| Website | http://rowe.com.au/ |
| Email | rowewa@rowe.com.au |

Emergency telephone number

| Association / Organisation | ROWE SCIENTIFIC | |
|-----------------------------------|--------------------------|--|
| Emergency telephone numbers | +61 8 9302 1911 (24 Hrs) | |
| Other emergency telephone numbers | Not Available | |

SECTION 2 Hazards identification

Classification of the substance or mixture

| Poisons Schedule Not Applicable | | |
|---------------------------------|---|--|
| Classification [1] | [1] Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1 | |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI | |

Label elements

Hazard pictogram(s)



| Signal word | Dange |
|-------------|-------|
| | |

| Hazard | statement(s) |
|--------|--------------|
|--------|--------------|

| H315 | Causes skin irritation. |
|------|----------------------------|
| H318 | Causes serious eye damage. |

Precautionary statement(s) Prevention

| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
|------|--|
| P264 | Wash all exposed external body areas thoroughly after handling. |

Chemwatch: 5647-26 Page 2 of 12 Issue Date: 20/12/2023 Version No: 4.1 Print Date: 20/12/2023

Multielement Standards in tartaric/ HCI/ NaCI

| P305+P351+P338 | P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
|----------------|---|--|
| P310 | Immediately call a POISON CENTER/doctor/physician/first aider. | |
| P302+P352 | IF ON SKIN: Wash with plenty of water. | |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. | |
| P362+P364 | Take off contaminated clothing and wash it before reuse | |

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|---------------|-----------|--|
| 7647-01-0 | <3 | bydrochloric acid |
| 7647-14-5 | <2 | sodium chloride |
| 87-69-4 | <2 | tartaric acid |
| 7439-89-6 | <0.1 | iron |
| Not Available | | containing one or more of |
| Not Available | | Aluminum, Silver, Arsenic, Boron, Barium, Beryllium, Bismuth, Calcium, Cadmium, Chromium, Cerium, Cobalt, Cesium, Copper, Dysprosium, |
| Not Available | | Erbium, Europium, Iron, Gallium, Gadolinium, Germanium, Holmium, Indium, Potassium, Lanthanum, Lithium, Lutetium, Magnesium, Manganese, |
| Not Available | | Molybdenum, Niobium, Neodymium, Nickel, Phosphorus, Lead, Praseodymium, Rubidium, Rhenium, Sulfur, Antimony, Selenium, Silicon, Samarium, Tin, |
| Not Available | | Strontium, Tantalum, Terbium, Tellurium, Thorium, Titanium, Thulium, Uranium, Tungsten, Yttrium, Ytterbium, Zinc |
| 7732-18-5 | Balance | water |
| 7697-37-2 | Trace | nitric acid |
| Legend: | 1 | by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. n drawn from C&L * EU IOELVs available |

SECTION 4 First aid measures

Description of first aid measures

| | •• |
|--------------|--|
| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

Chemwatch: 5647-26 Page 3 of 12

Version No: 4.1

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: 20/12/2023 Print Date: 20/12/2023

- There is no restriction on the type of extinguisher which may be used.
 Use extinguishing media suitable for surrounding area.

| special hazards arising from th | ne substrate or mixture |
|---------------------------------|--|
| Fire Incompatibility | Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
| dvice for firefighters | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. |
| Fire/Explosion Hazard | carbon dioxide (CO2) metal oxides other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes. Non combustible. Not considered a significant fire risk, however containers may burn. |

SECTION 6 Accidental release measures

HAZCHEM

Personal precautions, protective equipment and emergency procedures

Not Applicable

Decomposition may produce toxic fumes of:

See section 8

Environmental precautions

Methods and material for containment and cleaning up

| Minor Spills | Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. |
|--------------|---|
| Major Spills | Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect so/lde residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

| Precautions for safe handling | |
|-------------------------------|---|
| Safe handling | DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
| Other information | Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: **20/12/2023**Print Date: **20/12/2023**

Conditions for safe storage, including any incompatibilities

Suitable container

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

Storage incompatibility

Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|-------------------|-------------------|-------------------|------------------|-------------------|---------------|
| Australia Exposure Standards | hydrochloric acid | Hydrogen chloride | Not Available | Not Available | 5 ppm / 7.5 mg/m3 | Not Available |
| Australia Exposure Standards | nitric acid | Nitric acid | 2 ppm / 5.2 mg/m3 | 10 mg/m3 / 4 ppm | Not Available | Not Available |

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
|-------------------|---------------|---------------|---------------|
| hydrochloric acid | Not Available | Not Available | Not Available |
| hydrochloric acid | 1.8 ppm | 22 ppm | 100 ppm |
| sodium chloride | 0.5 ppm | 2 ppm | 20 ppm |
| tartaric acid | 1.6 mg/m3 | 17 mg/m3 | 100 mg/m3 |
| iron | 3.2 mg/m3 | 35 mg/m3 | 150 mg/m3 |
| nitric acid | Not Available | Not Available | Not Available |

| Ingredient | Original IDLH | Revised IDLH |
|-------------------|---------------|---------------|
| hydrochloric acid | 50 ppm | Not Available |
| sodium chloride | Not Available | Not Available |
| tartaric acid | Not Available | Not Available |
| iron | Not Available | Not Available |
| water | Not Available | Not Available |
| nitric acid | 25 ppm | Not Available |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|-----------------|---|----------------------------------|
| sodium chloride | Е | ≤ 0.01 mg/m³ |
| tartaric acid | E | ≤ 0.01 mg/m³ |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the | |

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Appropriate engineering controls

| Type of Contaminant: | Air Speed: |
|---|---------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |

Within each range the appropriate value depends on:

Lower end of the range Upper end of the range

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: 20/12/2023 Print Date: 20/12/2023

1: Room air currents minimal or favourable to capture 1: Disturbing room air currents 2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity 3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment









Eye and face protection

Safety glasses with side shields.

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact
- · chemical resistance of glove material,
- · glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended

Body protection

Hands/feet protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron. Barrier cream.
- Skin cleansing cream.
- ► Eve wash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

Multielement Standards in tartaric/ HCI/ NaCI

| Material | СРІ |
|----------|-----|
| BUTYL | С |

Respiratory protection

Type BE-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum | Half-Face | Full-Face | Powered Air |
|-------------------|------------|------------|-------------|
| Protection Factor | Respirator | Respirator | Respirator |

Page 6 of 12 Version No: 4.1 Multielement Standards in tartaric/ HCI/ NaCI

| С | up to 10 x ES | BE-ALIS P2 | _ | BE-PAPR-AUS / | |
|---|---------------|------------|---|---------------|--|

compounds(below 65 degC)

| up to 10 x ES | BE-AUS P2 | - | BE-PAPR-AUS / Class 1 P2 | | | |
|--|-----------|------------------------|-----------------------------|--|--|--|
| up to 50 x ES | - | BE-AUS / Class 1 P2 | - | | | |
| up to 100 x ES | - | BE-2 P2 | BE-PAPR-2 P2 ^ | | | |
| ^ - Full-face A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen. MB = Methyl bromide. AX = Low boiling point organic | | | | | | |

Issue Date: 20/12/2023

Print Date: 20/12/2023

| BUTYL/NEOPRENE | С |
|-------------------|---|
| HYPALON | С |
| NAT+NEOPR+NITRILE | С |
| NATURAL RUBBER | С |
| NATURAL+NEOPRENE | С |
| NEOPRENE | С |
| NEOPRENE/NATURAL | С |
| NITRILE | С |
| NITRILE+PVC | С |
| PE/EVAL/PE | С |
| PVA | С |
| PVC | С |
| SARANEX-23 | С |
| VITON | С |
| VITON/NEOPRENE | С |

^{*} CPI - Chemwatch Performance Index

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

Ansell Glove Selection

| Glove — In order of recommendation |
|------------------------------------|
| AlphaTec 02-100 |
| AlphaTec® 38-612 |
| AlphaTec® 53-001 |
| AlphaTec® 58-005 |
| AlphaTec® Solvex® 37-175 |
| BioClean™ Emerald BENS |
| BioClean™ Extra BLAS |
| BioClean™ Fusion (Sterile) S-BFAP |
| BioClean™ N-Plus BNPS |
| BioClean™ Ultimate BUPS |

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties

| Appearance | Liquid; mixes with water. | | |
|--|---------------------------|---|----------------|
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Applicable |
| pH (as supplied) | Not Available | Decomposition temperature (°C) | Not Applicable |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| nitial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
| Solubility in water | Miscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

^{*} Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner

Chemwatch: **5647-26**Version No: **4.1**

Page 7 of 12

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: 20/12/2023
Print Date: 20/12/2023

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhaled Hydrogen chloride (HCl) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes.

Inhalation of HCI may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Fluid on the lungs followed by generalised lung damage may follow.

Breathing of HCl vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease.

High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver.

Ingestion Accidental ingestion of the material may be damaging to the health of the individual.

Skin Contact

Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

The material may accentuate any pre-existing dermatitis condition

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.

Eye

Chronic

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and

gums; and ulceration of the nasal mucous membranes.

Repeated exposures of animals to concentrations of about 34 ppm HCl produced no immediate toxic effects.

Workers exposed to hydrochloric acid suffered from gastritis and a number of cases of chronic bronchitis have also been reported.

Repeated or prolonged exposure to dilute solutions of HCl may cause dermatitis.

| Multielement Standards in | TOXICITY | IRRITATION |
|----------------------------------|--|--|
| tartaric/ HCI/ NaCI | Not Available | Not Available |
| hydrochloric acid | TOXICITY | IRRITATION |
| | dermal (mouse) LD50: 1449 mg/kg ^[2] | Eye (rabbit): 5mg/30s - mild |
| | Oral (Rat) LD50: 900 mg/kg ^[2] | Eye: adverse effect observed (irritating) ^[1] |
| | | Skin: adverse effect observed (corrosive) ^[1] |
| | | Skin: adverse effect observed (irritating) ^[1] |
| | TOXICITY | IRRITATION |
| | TOXICITY | indifference of the second sec |
| | Dermal (rabbit) LD50: >10000 mg/kg ^[1] | Eye (rabbit): 10 mg - moderate |
| sodium chloride | | |
| sodium chloride | Dermal (rabbit) LD50: >10000 mg/kg ^[1] | Eye (rabbit): 10 mg - moderate |
| sodium chloride | Dermal (rabbit) LD50: >10000 mg/kg ^[1] Inhalation(Rat) LC50: >10.5 mg/l4h ^[1] | Eye (rabbit): 10 mg - moderate Eye (rabbit):100 mg/24h - moderate |
| sodium chloride tartaric acid | Dermal (rabbit) LD50: >10000 mg/kg ^[1] Inhalation(Rat) LC50: >10.5 mg/l4h ^[1] Oral (Rat) LD50: 3000 mg/kg ^[2] | Eye (rabbit): 10 mg - moderate Eye (rabbit):100 mg/24h - moderate Skin (rabbit): 500 mg/24h - mild |

Chemwatch: **5647-26** Page **8** of **12**

Version No: 4.1

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: **20/12/2023**Print Date: **20/12/2023**

| iron | TOXICITY | IRRITATION |
|-------------|--|--|
| | Oral (Rat) LD50: 98600 mg/kg ^[2] | Not Available |
| | TOXICITY | IRRITATION |
| water | Oral (Rat) LD50: >90000 mg/kg ^[2] | Not Available |
| | TOXICITY | IRRITATION |
| nitric acid | Inhalation(Rat) LC50: 0.13 mg/L4h ^[2] | Eye: adverse effect observed (irritating) ^[1] |
| | | Skin: adverse effect observed (corrosive) ^[1] |

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

HYDROCHLORIC ACID

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

SODIUM CHLORIDE

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Convulsions, haemorrhage recorded.

for simple alpha-hydroxy carboxylic acids and their salts:

The US Food and Drug Administration (FDA) received a total of 114 adverse dermatologic experience reports for alpha-hydroxy acids (AHA)-containing skin care products between 1992 and February 2004, with the maximum number in 1994. The reported adverse experiences included burning (45), dermatitis or rash (35), swelling (29), pigmentary changes (15), blisters or welts (14), skin peeling (13), itching (12), irritation or tenderness (8), chemical burns (6), and increased sunburn (3). The frequency of such reports for skin exfoliating products that contain AHAs has been considerably lower in subsequent years. The more serious adverse reactions appear to occur most often with products that cause the greatest degree of exfoliation, such as "skin peelers."

Various studies confirmed previous industry studies indicating that applying AHAs to the skin results in increased UV sensitivity. After four weeks of AHA application, volunteers' sensitivity to skin reddening produced by UV increased by 18 percent. Similarly, the volunteers' sensitivity to UV-induced cellular damage doubled, on average, with considerable differences among individuals. Topical glycolic acid enhances photodamage by ultraviolet light.

However, the studies also indicated that this increase in sensitivity is reversible and does not last long after discontinuing use of the AHA cream. One week after the treatments were halted, researchers found no significant differences in UV sensitivity among the various skin sites.

Most AHAs are physiologic, natural, and non-toxic substances. All members of the group promote normal keratinization and desquamation.

Those with multiple hydroxyl groups are moisturizing antioxidants, and are especially gentle for sensitive skin.

The studies did not identify exactly how AHAs bring about the increased UV sensitivity, although the effects did not appear to involve dramatic increases in UV-induced damage to DNA in the skin.

Previous FDA studies have indicated that a cosmetic-type cream base caused an AHA to penetrate more deeply into the skin when compared to an AHA solution without the usual cosmetic ingredients. However, further studies will be needed to learn how much, if at all, those cosmetic-type ingredients influence the AHA-related effects on UV sensitivity.

TARTARIC ACID

The toxicology of simple alpha hydroxy carboxylic acids cluster is characterised by five compounds sharing the functional group defining the cluster name

Experimental data available for members of the simple alpha-hydroxy carboxylic acids indicate a low acute, repeated-dose, reproductive and developmental toxicity.

The simple alpha hydroxy carboxylic acids are eye and skin irritants but are not expected to be skin sensitisers.

Genotoxicity test data for two cluster members and a cancer bioassay for the calcium salt of propanoic acid, 2-hydroxy- yielded negative results and all other cluster members are considered to have little or no mutagenic or carcinogenic potential.

Acute oral toxicity of propanoic acid, 2-hydroxy- (2S)- (79-33-4) and propanoic acid, 2-hydroxy- (50-21-5) are low. The repeated-dose and developmental toxicity of the three tested simple alpha -hydroxy carboxylic acids is low. In EPA's High Production Volume Program, reproductive toxicity testing for propanoic acid, 2-hydroxy- (50-21-5) was deemed unnecessary because it is a normal component of human intermediary metabolism. Reproductive toxicity of acetic acid, 2-hydroxy- (79-14-1) has been tested and was found to be low. Low reproductive toxicity of the associated potassium salts is also expected to be low. Alpha-hydroxy carboxylic acids are severe eye irritants. Acetic acid, 2-hydroxy- (79-14-1), propanoic acid, 2-hydroxy- (2S)- (79-33-4) and propanoic acid, 2-hydroxy- (50-21-5) all produced positive skin irritation in rabbits. The members of this cluster are not expected to be skin sensitisers based on negative results in guinea pigs for both acetic acid, 2-hydroxy- (79-14-1) and propanoic acid, 2-hydroxy- (2S)- (79-33-4). Genotoxicity data for acetic acid, 2-hydroxy-(79-14-1) and propanoic acid, 2-hydroxy- (50-21-5) in rational for acetic acid, 2-hydroxy- (79-14-1) and propanoic acid, 2-hydroxy- (50-21-5) in rational for acetic acid, 2-hydroxy- (100-21-5) in rational for acetic acid, 2-hydroxy- (100-21-5)

Some products containing alpha-hydroxy acids (AHAs) have been marketed for uses such as treating acne, removing scars, and lightening discolorations. Among these are some products marketed as "skin peelers," which may contain relatively high concentrations of AHAs or other acids and are designed to remove the outer layer of the skin

Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce respiratory tract irritation. Symptoms of pulmonary irritation may include coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and a burning sensation.

Unlike most organs, the lung can respond to a chemical insult or a chemical agent, by first removing or neutralising the irritant and then repairing the damage (inflammation of the lungs may be a consequence).

The repair process (which initially developed to protect mammalian lungs from foreign matter and antigens) may, however, cause further damage to the lungs (fibrosis for example) when activated by hazardous chemicals. Often, this results in an impairment of gas exchange, the primary function of the lungs. Therefore prolonged exposure to respiratory irritants may cause sustained breathing difficulties.

NITRIC ACID

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: **20/12/2023**Print Date: **20/12/2023**

The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent **HYDROCHLORIC ACID &** asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible **SODIUM CHLORIDE &** airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal **TARTARIC ACID & NITRIC** lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to ACID the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. **HYDROCHLORIC ACID &** No significant acute toxicological data identified in literature search. for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airways from direct exposure to inhaled acidic mists, just as mucous plays an important role in protecting the gastric epithelium from its auto-secreted hydrochloric **HYDROCHLORIC ACID &** acid. In considering whether pH itself induces genotoxic events in vivo in the respiratory system, comparison should be made with the human NITRIC ACID stomach, in which gastric juice may be at pH 1-2 under fasting or nocturnal conditions, and with the human urinary bladder, in which the pH of urine can range from <5 to > 7 and normally averages 6.2. Furthermore, exposures to low pH in vivo differ from exposures in vitro in that, in vivo, only a portion of the cell surface is subjected to the adverse conditions, so that perturbation of intracellular homeostasis may be maintained more readily than in vitro. **Acute Toxicity** Carcinogenicity × Skin Irritation/Corrosion Reproductivity Serious Eye Damage/Irritation STOT - Single Exposure × Respiratory or Skin × × STOT - Repeated Exposure sensitisation

Legend:

Aspiration Hazard

Data either not available or does not fill the criteria for classification
 Data available to make classification

SECTION 12 Ecological information

Mutagenicity

Toxicity

| Multielement Standards in | Endpoint | Test Duration (hr) | Species | Va | lue | Source |
|---------------------------|------------------|--------------------|-------------------------------|--------------|----------------|-----------------|
| tartaric/ HCI/ NaCI | Not Available | Not Available | Not Available | No Av | ot railable | Not Availabl |
| | Endpoint | Test Duration (hr) | Species | Valu | е | Sourc |
| hydrochloric acid | LC50 | 96h | Fish | 334. | 734mg/L | 4 |
| | EC50(ECx) | 9.33h | Fish | 0.51 | mg/L | 4 |
| | Endpoint | Test Duration (hr) | Species | Value | | Source |
| | EC50 | 72h | Algae or other aquatic plants | 20.76-36.17r | ng/L | 4 |
| | EC50 | 48h | Crustacea | 0.00439-0.00 | 565mg/l | 4 |
| sodium chloride | EC50 | 96h | Algae or other aquatic plants | 1110.36mg/L | | 4 |
| | LC50 | 96h | Fish | 1000mg/l | | 4 |
| | NOEC(ECx) | 6h | Fish | 0.001mg/l | | 4 |
| | Endpoint | Test Duration (hr) | Species | Va | lue | Sour |
| | EC50 | 72h | Algae or other aquatic plant | s 51. | 404mg/l | 2 |
| 4-4-4 | EC50 | 48h | Crustacea | 93. | 313mg/l | 2 |
| tartaric acid | EC50 | 96h | Algae or other aquatic plant | s 230 | 616mg/L | 2 |
| | NOEC(ECx) | 72h | Algae or other aquatic plant | s 3.1 | 25mg/l | 2 |
| | LC50 | 96h | Fish | >10 | 00mg/l | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | | Sour |
| | EC50 | 72h | Algae or other aquatic plants | 18mg/l | | 2 |
| iron | EC50 | 48h | Crustacea | >100mg/l | | 2 |
| | LC50 | 96h | Fish | 0.00499-0.00 | 819mg/l | 4 |
| | NOEC(ECx) | 48h | Algae or other aquatic plants | 0.1-4mg/l | | 4 |
| | Endpoint | Test Duration (hr) | Species | Va | ilue | Source |
| water | Not Available | Not Available | Not Available | No | ot railable | Not Availab |

Chemwatch: **5647-26** Page **10** of **12**

Version No: 4.1

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: **20/12/2023**Print Date: **20/12/2023**

| | Endpoint | Test Duration (hr) | Species | Value | Source |
|-------------|---|--------------------|-----------|------------|--------|
| | EC50 | 48h | Crustacea | 490mg/l | 2 |
| nitric acid | LC50 | 96h | Fish | 102.24mg/L | 4 |
| | EC50(ECx) | 96h | Crustacea | 39mg/l | 2 |
| Legend: | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan - Bioconcentration Data 8. Vendor Data | | | | |

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-------------------|-------------------------|------------------|
| hydrochloric acid | LOW | LOW |
| sodium chloride | LOW | LOW |
| tartaric acid | LOW | LOW |
| water | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|-------------------|------------------------|
| hydrochloric acid | LOW (LogKOW = 0.5392) |
| sodium chloride | LOW (LogKOW = 0.5392) |
| tartaric acid | LOW (LogKOW = -1.0017) |

Mobility in soil

| Ingredient | Mobility |
|-------------------|------------------|
| hydrochloric acid | LOW (KOC = 14.3) |
| sodium chloride | LOW (KOC = 14.3) |
| tartaric acid | HIGH (KOC = 1) |

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- Product / Packaging disposal
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 Transport information

Labels Required

| Marine Pollutant | NO |
|------------------|----------------|
| HAZCHEM | Not Applicable |

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|-------------------|---------------|
| hydrochloric acid | Not Available |
| sodium chloride | Not Available |
| tartaric acid | Not Available |
| iron | Not Available |
| water | Not Available |
| nitric acid | Not Available |

Page 11 of 12 Issue Date: 20/12/2023 Print Date: 20/12/2023 Multielement Standards in tartaric/ HCI/ NaCI

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|-------------------|---------------|
| hydrochloric acid | Not Available |
| sodium chloride | Not Available |
| tartaric acid | Not Available |
| iron | Not Available |
| water | Not Available |
| nitric acid | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

hydrochloric acid is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

sodium chloride is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

tartaric acid is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

iron is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 $\,$

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

nitric acid is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

National Inventory Status

| lational inventory Status | | | |
|--|--|--|--|
| National Inventory | Status | | |
| Australia - AIIC / Australia Non-Industrial Use | Yes | | |
| Canada - DSL | Yes | | |
| Canada - NDSL | No (hydrochloric acid; sodium chloride; tartaric acid; iron; water; nitric acid) | | |
| China - IECSC | Yes | | |
| Europe - EINEC / ELINCS / NLP | Yes | | |
| Japan - ENCS | No (iron) | | |
| Korea - KECI | Yes | | |
| New Zealand - NZIoC | Yes | | |
| Philippines - PICCS | Yes | | |
| USA - TSCA | Yes | | |
| Taiwan - TCSI | Yes | | |
| Mexico - INSQ | Yes | | |
| Vietnam - NCI | Yes | | |
| Russia - FBEPH | Yes | | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. | | |

SECTION 16 Other information

Revision Date

20/12/2023

Multielement Standards in tartaric/ HCI/ NaCI

Issue Date: **20/12/2023**Print Date: **20/12/2023**

Initial Date

07/12/2023

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|-------------------|---|
| 3.1 | 18/12/2023 | Name |
| 4.1 | 20/12/2023 | Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (skin), Toxicological information - Chronic Health, Hazards identification - Classification, Disposal considerations - Disposal, Exposure controls / personal protection - Engineering Control, Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire fighting), Firefighting measures - Fire Fighter (fire incompatibility), First Aid measures - First Aid (eye), First Aid measures - First Aid (inhaled), First Aid measures - First Aid (syallowed), Handling and storage - Handling Procedure, Composition / information on ingredients - Ingredients, Stability and reactivity - Instability Condition, Exposure controls / personal protection - Personal Protection (other), Exposure controls / personal protection - Personal Protection (hands/feet), Accidental release measures - Spills (major), Handling and storage - Storage (storage incompatibility) |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- ► IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ► IDLH: Immediately Dangerous to Life or Health Concentrations
- ► ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- ► OTV: Odour Threshold Value
- ► BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ► DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ► DSL: Domestic Substances List
- ► NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ► EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ► ENCS: Existing and New Chemical Substances Inventory
- ► KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ► INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.